

Heavy Weight Concealed Bearing **LifeSpan**®


CB138 (ANSI A8211) Steel – polished and plated or phosphated and prime coated for painting

CB98 (ANSI A2211) Brass or bronze – polished and plated or painted

CB98 (32) (ANSI A5211) Stainless steel – highly polished

CB98 (32D) (ANSI A5211) Stainless steel – satin finish

- For heavy or high frequency hollow metal or wood doors hung on channel iron frames
- Concealed LifeSpan® bearing is maintenance free – no oil, no grease
- Pins in non-ferrous hinges are stainless steel
- Reversible flush tips and pins
- Hinges can be furnished with hospital tips (HT)
- LifeSpan® limited lifetime warranty



Measurements below

Size Length of Joint	Width				Offset (C)	Gauge of Metal	Flat Head Machine Screws/Per Piece		Quantity Per Box	Quantity Per Case	Case Weight				
	Frame Leaf (A)		Door Leaf (B)				Frame Leaf	Door Leaf			Bronze Lbs. (Kg)	Steel Lbs. (Kg)			
	Inches	(mm)	Inches	(mm)									Inches	(mm)	
4 1/2	(114)	1 1/2	(38.1)	2 1/8	(54)	1/2	(12.7)	.180	(4.6)	3-12-24 X 1/2	4-12-24 X 1/2	3 EA.	30 EA.	36 (17)	36 (17)
5	(127)	1 1/2	(38.1)	2 1/8	(54)	1/2	(12.7)	.190	(4.8)	4-12-24 X 1/2	4-12-24 X 1/2	3 EA.	24 EA.	36 (17)	36 (17)
6	(152)	1 1/2	(38.1)	2 1/8	(54)	1/2	(12.7)	.203	(5.2)	4-1/4-20 X 1/2	5-1/4-20 X 2	3 EA.	24 EA.	48 (22)	48 (22)