

3 KNUCKLE HALF MORTISE HINGES

Standard Weight Concealed Bearing **LifeSpan**[®]


CB1920R – (ANSI A8212) Steel – polished and plated or phosphated and prime coated for painting

CB1980R – (ANSI A2212) Brass or bronze – polished and plated or painted

CB1980R (32) – (ANSI A5212) Stainless steel – highly polished

CB1980R (32D) – (ANSI A5212) Stainless steel – satin finish

- For medium weight hollow metal, or wood doors of average frequency, hung on channel iron frames
- Concealed LifeSpan[®] bearing for trouble-free, long life – no oil, no grease, no maintenance
- Pins in nonferrous hinges are stainless steel
- Reversible flush tips and pins
- Hinges can be furnished with hospital tips (HT)
- LifeSpan[®] limited lifetime warranty
- Available with exposed tips (ET)



Measurements below

Size Length of Joint	Width		Offset (C)	Gauge of Metal	Flat head Machine Screws/Per Piece		Quantity Per Box	Quantity Per Case	Case Weight	
	Frame Leaf (A)	Door Leaf (B)			Frame Leaf	Door Leaf			Bronze Lbs. (Kg)	Steel Lbs. (Kg)
4 1/2 (114)	1 1/2 (38.1)	2 1/16 (52.4)	7/16 (11.1)	.134 (3.4)	3-12-24 X 1/2	4-12-24 X 1/2	3 EA.	30 EA.	30 (14)	24 (11)
5 (127)	1 1/2 (38.1)	2 1/16 (52.4)	7/16 (11.1)	.146 (3.7)	4-12-24 X 1/2	4-12-24 X 1/2	3 EA.	24 EA.	37 (17)	31 (14)