

3 KNUCKLE HALF MORTISE HINGES

Heavy Weight Concealed Bearing **LifeSpan**[®]


CB1921R – (ANSI A8211) Steel – polished and plated or phosphated and prime coated for painting

CB1981R – (ANSI A2211) Brass or bronze – polished and plated or painted

CB1981R (32) – (ANSI A5211) Stainless steel – highly polished

CB1981R (32D) – (ANSI A5211) Stainless steel – satin finish

- For heavy, or high frequency hollow metal, or wood doors, hung on channel iron frames
- Concealed LifeSpan[®] bearing for trouble-free, long life – no oil, no grease, no maintenance
- Pins in nonferrous hinges are stainless steel
- Reversible flush tips and pins
- Hinges can be furnished with hospital tips (HT)
- LifeSpan[®] limited lifetime warranty
- Available with exposed tips (ET)



Measurements below

Size Length of Joint	Width		Offset		Gauge of Metal	Flat head Machine Screws/Per Piece		Quantity Per Box	Quantity Per Case	Case Weight	
	Frame Leaf (A)	Door Leaf (B)	Inches (C)	Inches		Frame Leaf	Door Leaf			Bronze Lbs. (Kg)	Steel Lbs. (Kg)
4 1/2 (114)	1 1/2 (38.1)	2 1/8 (54)	1/2 (12.7)	.180 (4.6)	3-12-24 X 1/2	4-12-24 X 1/2	3 EA.	30 EA.	36 (17)	36 (17)	
5 (127)	1 1/2 (38.1)	2 1/8 (54)	1/2 (12.7)	.190 (4.8)	4-12-24 X 1/2	4-12-24 X 1/2	3 EA.	24 EA.	36 (17)	36 (17)	
6 (152)	1 1/2 (38.1)	2 1/8 (54)	1/2 (12.7)	.203 (5.2)	4-1/4-20 X 1/2	5-1/4-20 X 1/2	3 EA.	24 EA.	48 (22)	48 (22)	