

CABINET AND WARDROBE HARDWARE

Cabinet Pulls

4483 1/2, 4484, 4485 – (ANSI B02011) – solid brass – polished and plated
4483 1/2, 4484 – (ANSI B02011) – aluminum – satin finish

- For cabinet doors and drawers up to 3/4" (19 mm) thick
- Very acceptable for Bi-Fold doors
- 1" (25.4 mm) finger clearance on all sizes
- 1 5/16" (33.2 mm) projection
- 5/16" (7.9 mm) diameter
- Referred to as wire pulls



4483 1/2



4484



4485

Catalog Number	Screws Hole Spacing		Machine Screws/ Per Piece	Pieces Per Box	Pieces Per Case	Case Weight	
	Inches	(mm)				Brass Lbs. (KG)	Aluminum Lbs. (Kg)
4483 1/2 and 4483 1/2 Alum.	3 1/2	(89)	2-8-32 x 1	25	100	16 (7)	7 (3)
4484 and 4484 Alum.	4	(102)	2-8-32 x 1	25	100	17 (8)	8 (4)
4485	5	(127)	2-8-32 x 1	25	100	20 (9)	-

Cabinet Knobs

4482 – (ANSI B02131) – solid brass – polished and plated

- For cabinet doors and drawers up to 3/4" (19 mm) thick
- Can be used on Bi-Fold doors
- 1 5/16" (33.2 mm) projection



Catalog Number	Size Diameter		Flat Head Wood Screws/ Per Pack	Pieces Per Box	Pieces Per Case	Carton Weight	
	Inches	(mm)				Lbs. (Kg)	(Kg)
4482	1 1/4	(32)	1- 8-32 x 1	25	100	11	(5)