

**Heavy Weight Ball Bearing**


**FBB138** (ANSI A8211) – Steel – polished and plated or phosphated and prime coated for painting

**FBB98** (ANSI A2211) – Brass or bronze – polished and plated or painted

**FBB98 (32)** (ANSI A5211) – Stainless steel – highly polished

**FBB98 (32D)** (ANSI A5211) – Stainless steel – satin finish

- For heavy or high frequency hollow metal or wood doors hung on channel iron frames
- Equipped with four Stanley permanently lubricated non-detachable ball bearings
- Pins in non-ferrous hinges are stainless steel
- Reversible flush tips and pins
- Hinges can be furnished with hospital tips (HT)



Measurements below

Size Length of Joint	Width		Offset		Gauge of Metal	Flat Head Machine Screws/Per Piece		Quantity Per Box	Quantity Per Case	Case Weight	
	Frame Leaf (A)	Door Leaf (B)	(C)			Frame Leaf	Door Leaf			Bronze Lbs. (Kg)	Steel Lbs. (Kg)
4 1/2 (114)	1 1/2 (38.1)	2 1/8 (54)	1/2 (12.7)	.180 (4.6)	3-12-24 X 1/2	4-12-24 X 1/2	3 EA.	30 EA.	36 (17)	36 (17)	
5 (127)	1 1/2 (38.1)	2 1/8 (54)	1/2 (12.7)	.190 (4.8)	4-12-24 X 1/2	4-12-24 X 1/2	3 EA.	24 EA.	36 (17)	36 (17)	
6 (152)	1 1/2 (38.1)	2 1/8 (54)	1/2 (12.7)	.203 (5.2)	4-1/4-20 X 1/2	5-1/4-20 X 1/2	3 EA.	24 EA.	48 (22)	48 (22)	