
## **Detention Hardware**

## **Triple Weight Concealed Ball Bearing Prison Hinges**

**BB852** – (ANSI A8391) – steel with welded pin. Phosphated and prime coated for painting

- For lead-lined doors to x-ray rooms and extremely heavy doors and gates
- For hinged cell-front doors and grated steel doors of penitentiaries, jails, reformatories, etc.
- Made of triple weight steel capable of carrying doors weighing up to 1200 lbs. (544 Kg) (Based on a 3' x 7' door with 3 hinges)
- Each of the 2 concealed hardened steel races contains sixteen 3/16" (4.8 mm) hardened and ground steel balls which are assembled within a jacket
- Provision has been made in the barrel of the hinge for forced lubrication if further lubrication is necessary
- Typically made not swaged, no holes (application A) for full surface applications, or for full mortise (applications C) application. All other configurations are made to order




Rolled knuckles are welded and machined.

Pin is solid one piece steel welded at both ends making pin removal impossible.


Two concealed bearing assemblies. Hardened raceways. Hardened and ground balls.




## **Typical applications of BB852**




## Full Surface with holes to template – application B





For all full mortise applications the center of barrel should be set 1 1/8" (28.6 mm) from door and frame so welded joints will clear. Leaves can be swaged apart any distance between 1/8" (3.2 mm) to 7/8" (22.2 mm)



Variations of half mortise or half surface types can be obtained by further bumping or swaging of mortise leaf to accommodate any required construction. Specify hand when ordering

<sup>\*</sup> Furnished on order with holes and with machine screws, at additional cost. If above details do not show your particular construction submit details and specifications

No holes, not swaged for	Catalog Number	USP/EDP Number	Length of Joint		Length of Joint		Gauge of Metal		Diameter of Pin		Quantity Per Carton	Carton Weight	
applications			Inches	(mm)	Inches	(mm)	Inches	(mm)	Inches	(mm)		Lbs.	(Kg)
"A" or "C"	BB852	02 9388	5	(127)	6	(152)	375	(9.5)	3/4	(19.1)	2 Ea.	10	(4.5)