

3 Knuckle Half Mortise Hinges

Standard Weight Concealed Bearing

CB1920R – (ANSI A8212) Steel – polished and plated or phosphated and prime coated for painting


CB1980R – (ANSI A2212) Brass or bronze – polished and plated or painted

CB1980R (32) – (ANSI A5212) Stainless steel – highly polished

CB1980R (32D) – (ANSI A5212) Stainless steel – satin finish



- For medium weight hollow metal, or wood doors of average frequency, hung on channel iron frames
- Concealed bearing for trouble-free, long life – no oil, no grease, no maintenance
- Pins in nonferrous hinges are stainless steel
- Reversible flush tips and pins
- Hinges can be furnished with hospital tips (HT)
- Limited lifetime warranty
- Available with exposed tips (ET)



Measurements below

Size Length of Joint	Width		Offset (C)	Gauge of Metal	Flat Head Screws Per Piece		Quantity Per Box	Quantity Per Case	Case Weight	
	Frame Leaf (A)	Door Leaf (B)			Frame Leaf	Door Leaf			Bronze	Steel
	Inches (mm)	Inches (mm)			Inches (mm)	Inches (mm)			Lbs. (Kg)	Lbs. (Kg)
4 1/2 (114)	1 1/2 (38.1)	2 1/16 (52.4)	7/16 (11.1)	.134 (3.4)	3-12-24 x 1/2	4-12-24 x 1/2	3 ea.	30 ea.	30 (14)	24 (11)
5 (127)	1 1/2 (38.1)	2 1/16 (52.4)	7/16 (11.1)	.146 (3.7)	4-12-24 x 1/2	4-12-24 x 1/2	3 ea.	24 ea.	37 (17)	31 (14)